



- LEGEND :**
1. PRESSED STEEL ACOUSTIC FRAME.
 2. FIRE RATED PERIMETER SYNPRENE SEAL SHIPPED BY AMBICO, INSTALLED ON SITE BY OTHERS.
 3. PERIMETER SMOKE SEAL, SHIPPED BY AMBICO, INSTALLED ON SITE BY OTHERS.
 4. INTUMESCENT STRIP, SHIPPED BY AMBICO, INSTALLED ON SITE BY OTHERS.
 5. HINGES, BY OTHERS.
 6. INTUMESCENT HINGE PROTECTION , SHIPPED BY AMBICO, INSTALLED ON SITE BY OTHERS.
 7. HINGE REINFORCEMENT, FACTORY WELDED IN FRAME.
 8. ACOUSTIC MULLION IS REQUIRED. (FIXED OR REMOVABLE)
 9. BRACKET AND ADDITIONAL PERIMETER SEALS TO BE FITTED AND FASTENED TO HEADER AT SITE.
 10. 1/4" HIGH FLAT ACOUSTIC THRESHOLD 5" WIDTH, TO BE INSTALLED ON FINISHED FLOOR.

NOTES :
 - FRAME MUST BE INSTALLED AT FINISHED FLOOR HEIGHT.
 (DO NOT EMBED IN FLOOR).



TYPICAL ACOUSTIC STEEL PAIRED FRAME AND PERIMETER SEALS FOR FIRE RATED WOOD DOORS – STC 50